

# A/C SYSTEM SPECIFICATIONS

## Article Text

1994 Suzuki Swift

For Xeon

Copyright © 1998 Mitchell Repair Information Company, LLC

Tuesday, December 02, 2003 06:38PM

### ARTICLE BEGINNING

1994 AIR CONDITIONING & HEAT  
Suzuki A/C System Specifications

Samurai, Sidekick, Swift

### A/C SYSTEM SPECIFICATIONS

#### MANUAL A/C SYSTEM SPECIFICATIONS TABLE

---

Application	Specification
Compressor Type .....	Nippondenso 10-Cyl.
Compressor Belt Deflection (1)	
Samurai .....	13/32-15/32" (10-12 mm)
Sidekick .....	1/4-23/64" (6.5-9.0 mm)
Swift .....	21/64-13/32" (8-10 mm)
System Oil Capacity .....	2.0-3.4 ozs.
Refrigerant Capacity (2)	
R-12	
Samurai & Swift .....	17.6 ozs.
R-134a	
Samurai & Swift .....	17.6 ozs.
Sidekick .....	21.2 ozs.
System Operating Pressures (2)	
R-12	
High Side .....	206-213 psi (14.5-15.0 kg/cm <sup>2</sup> )
Low Side .....	21-28 psi (1.5-2.0 kg/cm <sup>2</sup> )
R-134a	
High Side .....	256-313 psi (18.0-22.0 kg/cm <sup>2</sup> )
Low Side .....	21-28 psi (1.5-2.0 kg/cm <sup>2</sup> )

(1) - With 22 lbs. (10 kg) pressure applied at belt center.

(2) - Swift and Samurai may use either R-12 or R-134a refrigerant.  
Check underhood A/C specification label or A/C compressor label  
prior to servicing vehicle.

---

### END OF ARTICLE